



## CAT CB34 ASPHALT COMPACTOR

### FEATURES & BENEFITS

#### Caterpillar C2.2 Engine

The C2.2 engine provides efficient power while meeting U.S. EPA Tier 4a engine emission requirements.

#### Operator's Station

The convenient, comfortable operating environment with three-position seating provides good visibility and promotes day-long productivity.

#### Vibratory System

The vibratory system provides good balance between frequency and amplitude in order to meet various job site conditions.

#### Water Spray System

Corrosion-proof components provide long life and reliable operation.

#### Reliability and Serviceability

The CB34 machines provide the reliability and serviceability that you've come to expect from Caterpillar.

### SPECIFICATIONS

#### Engine

Engine Model	Cat C2.2
Gross Power	46 hp
Net Power - ISO 9249	45 hp
Bore	3.3 in
Stroke	3.94 in

#### Weights

Operating Weight with ROPS/FOPS	8,688 lbs
Operating Weight at Rear Drum with ROPS/FOPS	4,410 lbs
Operating Weight at Front Drum with ROPS/FOPS	4,278 lbs

#### Service Refill Capacities

Fuel Tank Capacity	15.07 gal
Water (Spray) Tank Capacity	79.25 gal

#### Operating Specifications

Curb Clearance	23.5 in
Turning Radius Outside Drum Edge	169 in
Turning Radius Inside Drum Edge	118 in
Ground Clearance	11 in
Travel Speed Max	8 mph

#### Vibratory System

Drum Width	51 in
Drum Diameter	31 in
Frequency	4,140 vpm
Nominal Amplitude - High	0.01 in
Centrifugal Force Maximum	7,448 lbs
Vibration Selection	Front, rear or both
Eccentric Weight Drive	Hydraulic

#### Dimensions

Overall Length	123 in
Wheelbase	91 in
Height at Steering Wheel	72 in
Height with ROPS/FOPS	100 in
Compaction Width	51 in
Overall Width	55 in