

Date of printing 12/22/2022

Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max	30865 - 41890 lb	
Max bucket width	67 in	
Max breakout force	31475 lbf	
Max breakout torque	147510 ft.lb	
Weight (from)	1146 lb	
Tilt angle (2x)	40°	
Rotation speed (1 rotation per)	7.0 s at 19 gpm	
Working pressure	3626 psi	
Max return line pressure	290 psi at 26 gpm	
Min hydraulic flow	31.96 gpm	
Number of lubrication points	6	
Turning torque	7044 ft.lb at 3626 psi	
Tilt torque singe-acting cylinders	22790 ft.lb	
Tilt torque double acting cylinders	33265 ft.lb	



Dimensions

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
31,5 in	45,28 in	31,5 in	20,87 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.



